

## 8,7/15 kV

XLPE INSULATED, FLAT STEEL ROD SHIELD WITH ALUMINUM CONDUCTOR, SINGLE CORE MEDIUM VOLTAGE POWER CABLES



**YAXC8VZ3V-R (TSE),  
NA2XSEYFGbY(VDE)**

<b>Code</b>	YAXC8VZ3V-R (TSE), NA2XSEYFGbY(VDE)
<b>Standards</b>	TSE IEC 60502-2, Technical Specs, VDE 0276
<b>Construction</b>	Aluminum Conductor, Inner semi-conductor, XLPE insulation, Outer Semi-Conductor, Semi-Conductor Tape, Copper Shield, PVC Filler, PVC Separator Sheath, Galvanized Flat Steel Rod Shield, Galvanized Steel Helix Tape, PVC Outer Sheath
<b>Applications</b>	Used in Under heavy operating conditions, Underground, Power centers, Switchgear, City networks, Industrial facilities, Underground and cable channel.
<b>Technical Datas</b>	Max. Operating Temp. 90°C Max. Short Circuit Temp. 250°C For Max. 5 Sec Min. Bending Radius 15*D D:Cable Overall Diameter (mm)

Dimensions and Weight					Electrical Informations				
Nominal Cross Section	Overall Diameter	Net Weight	Standard Delivery Length	Standard Delivery Reel Size	Conductor DC (Max.) Resistance at 20 °C	Inductance per conductor (Appr.)	Operating Capacity (Appr.) at 20 °C	Current Carrying Capacity In (Appr.)	
(mm <sup>2</sup> )	(mm)	(kg/km)	(m)	(cm)	(ohm/km)	(mH/km)	(µF/km)	Ground (A) at 20°C	Air (A) at 30°C
3x35/16 rm	56,0	4400	1000	240	0,868	0,40	0,18	140	133
3x50/16 rm	59,0	4900	500	220	0,641	0,38	0,19	160	150
3x70/16 rm	63,0	5500	500	220	0,443	0,36	0,22	195	190
3x95/16 rm	67,0	6200	500	220	0,320	0,34	0,24	235	238
3x120/16 rm	70,0	7000	500	240	0,253	0,33	0,27	275	274
3x150/25 rm	74,0	7700	500	240	0,206	0,32	0,29	305	309
3x185/25 rm	77,0	8600	500	260	0,1640	0,31	0,31	345	354
3x240/25 rm	84,0	10000	250	220	0,1250	0,30	0,34	410	415
3x300/25 rm	89,0	11500	250	220	0,1000	0,29	0,38	460	500
3x400/35 rm	95,0	13100	250	240	0,0788	0,28	0,41	520	560

rm : Stranded Conductor