

12/20 kV

XLPE INSULATED, FLAT STEEL ROD SHIELD WITH ALUMINUM CONDUCTOR, SINGLE CORE MEDIUM VOLTAGE POWER CABLES



**YAXC8VZ3V-R (TSE),
NA2XSEYFGbY(VDE)**

Code	YAXC8VZ3V-R (TSE), NA2XSEYFGbY(VDE)
Standards	TSE IEC 60502-2, Technical Specs, VDE 0276
Construction	Aluminum Conductor, Inner semi-conductor, XLPE insulation, Outer Semi-Conductor, Semi-Conductor Tape, Copper Shield , PVC Filler, PVC Separator Sheath, Galvanized Flat Steel Rod Shield, Galvanized Steel Helix Tape, PVC Outer Sheath
Applications	Used in Under heavy operating conditions, Underground, Power centers, Switchgear, City networks, Industrial facilities, Underground and cable channel.
Technical Data	Max. Operating Temp. 90°C Max. Short Circuit Temp. 250°C For Max. 5 Sec Min. Bending Radius 15*D D:Cable Overall Diameter (mm)

Dimensions and Weight					Electrical Informations				
Nominal Cross Section	Overall Diameter	Net Weight	Standard Delivery Length	Standard Delivery Reel Size	Conductor DC (Max.) Resistance at 20 °C	Inductance per conductor (Appr.)	Operating Capacity (Appr.) at 20 °C	Current Carrying Capacity In (Appr.)	
(mm ²)	(mm)	(kg/km)	(m)	(cm)	(ohm/km)	(mH/km)	(µF/km)	Ground (A) at 20°C	Air (A) at 30°C
3x35/16 rm	61,0	5000	500	220	0,868	0,41	0,14	140	133
3x50/16 rm	64,0	5500	500	220	0,641	0,39	0,15	160	150
3x70/16 rm	68,0	6400	500	220	0,443	0,37	0,17	195	190
3x95/16 rm	72,0	7000	500	240	0,320	0,35	0,19	235	238
3x120/16 rm	76,0	7800	500	240	0,253	0,34	0,21	275	274
3x150/25 rm	79,0	8500	500	240	0,206	0,32	0,22	305	309
3x185/25 rm	84,0	9000	500	260	0,1640	0,31	0,24	345	354
3x240/25 rm	90,0	10700	250	220	0,1250	0,3	0,27	410	415
3x300/25 rm	96,0	12000	250	220	0,1000	0,29	0,29	460	500
3x400/35 rm	103,0	14000	250	240	0,0788	0,28	0,33	520	560

rm : Stranded Conductor